

ProREZ Coatings, LLC

P.O. Box 153, Cromwell, CT 06416-0153 877.511.3456 • www.prorezcoatings.com

Date Issued: 11/24/25 Version: 1.5

1. CHEMICAL PRODUCTS AND COMPANY IDENTIFICATION

Product Names/Trade Names: ProPoxy S Resin, ProPoxy SL Resin, ProPoxy MB Resin, ProPoxy UVR Resin,

ProPoxy Cove Resin, FlexPoxy Resin, EcoPoxy Resin, ProPoxy OPF Resin

Chemical Family: Bisphenol A Epoxy Resin, BioPoxy Resin

Manufacturer's Name: ProREZ Coatings, LLC

PO BOX 153

Cromwell, CT 06416-0153 USA

General No.: (877) 511-3456 (8:00am to 5:00pm Eastern Time)

Company 24 Hour Emergency Response Information: CHEMTEL: 1-800-255-3924

Emergency telephone numbers are to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals. All non-emergency questions should be directed to customer service.

2. HAZARDS IDENTIFICATION

Emergency Overview: WARNING! CAUSES EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. Do not breathe vapor or mist. Do not get on skin or clothing. Avoid contact with eyes. Wash thoroughly after handling.

Classification of the substance

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory/skin sensitization: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements: Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

Label Elements

Hazardous components that must be listed on the label:

Epoxy resin, May produce an allergic reaction.

Signal word: Warning

Pictograms:





Hazard Statements:

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash hands thoroughly after handling.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN: Wash with plenty of soap and water. P302+P352

Specific treatment (see warning on this label). P321

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash before reuse. P362

Wash contaminated clothing before reuse. P363

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. P337+P313

Collect spillage. P391

Dispose of contents/container IAW local, state, or federal regulations. P501

General Information: This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater. Repeated or prolonged contact causes sensitization, asthma and eczemas.

Read the entire SDS for a more thorough evaluation of the hazards.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	% By Weight	CAS Number
Bisphenol A-(epichlorhydrin), Bisphenol	60-100%	25085-99-8
A epoxy resin		

4. FIRST-AID MEASURES

General advice: Seek medical advice or medical attention if condition persists.

Eye contact: Rinse immediately with plenty of water for at least 15 minutes.

Skin Contact: Immediately remove any extraneous chemical, if possible without delay. Take off contaminated clothing and shoes immediately. Wash body off with soap and plenty of water.

Ingestion: Rinse mouth. Drink plenty of water. Never give anything by mouth to an unconscious person. If a person vomits when lying on his back, place him in the recovery position and turn victim's head to the side. Do not induce vomiting.



Inhalation: Move to fresh air. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.

Notes to Physician: No specific treatment. Treat symptomatically. Call the poison control center immediately if large quantities have been ingested.

5. FIRE-FIGHTING MEASURES

Suitable Fire Extinguishing Media: Water fog, foam, dry chemical, carbon dioxide.

Special Exposure Hazards: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Special Protective Equipment for Fire-Fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Danger of Explosion: This product does not present an explosion hazard

Flammable Limits: Not Available Explosion Limits: Not Available Auto-Ignition: Not Available

Flash Point: >200°C (>392°F) [DIN 51758 EN 22719 (Pensky-Martens Closed Cup)]

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental Precautions: Water polluting material. May be harmful to the environment if released in large quantities. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform authorities if the product has caused environmental pollution (sewers, drains, waterways or soil).

Methods for Cleaning up: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.



7. HANDLING AND STORAGE

Handling: Put on appropriate personal protective equipment, PPE (see Section 8). Eating and drinking should be prohibited in areas where this material is handled, stored and processed. Remove contaminated PPE or clothing, wash hands and face before eating and drinking. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Use only in area provided with appropriate exhaust ventilation. Empty containers retain product residue and can be hazardous. Do not get in eyes, skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment.

Storage: Store between 15-27°C (60-80°F) in accordance with local regulations away from sources of heat, ignition, and direct sunlight. Store in original container. Keep in a dry, well-ventilated area, and away from incompatible materials (see section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled or unapproved containers. Use appropriate containment to avoid environmental contamination.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Special Note for Exposure Control: Consult local authorities for acceptable exposure limits.

OSHA PEL (TWA): Not Determined ACGIH TLV (TWA): Not Determined NIOSH REL (TWA): Not Determined

Engineering measures: No special ventilation requirements. If possible work in ventilated area. Provide natural or explosion-proof fan to ensure adequate ventilation, especially in confined area. Avoid contact with skin, eyes, and clothing.

Environmental exposure controls: Construct a dike to prevent spreading. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Hygiene Measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating and drinking, smoking or using the lavatory and at the end of the working period. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location

Personal Protection:

Respiratory - In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Eyes – Splash proof safety glasses.

Skin - Rubber or plastic apron. Rubber or plastic gloves. Long sleeved clothing or wear protective sleeves. Remove and wash contaminated clothing before re-use.

Other protective equipment information - Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Neoprene gloves. PVC disposable gloves. Nitrile rubber. Butyl rubber. Impervious gloves. (The breakthrough time of the selected glove(s) must be greater than the intended use period.)

9. PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid
Odor:	Slightly/Faint Epoxy
Color:	Clear
PH Value:	7 [conc. (%w/w): 50%]
Boiling Point:	>200°C (>392°F)
Melting Point:	Not Available
Vapor Pressure (25°C):	Not Available
Vapor Density:	Not Available
Density (Nominal):	1.13
Solubility in water:	Insoluble
Evaporation Rate (Butyl Acetate = 1):	Not Available
Volatile Organic Compounds:	Nil

10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions. Hazardous reactions will not occur.

Conditions to avoid: No specific data.

Materials to avoid: Strong acids, strong bases, strong oxidizing agents.

Hazardous decomposition products: Under normal conditions hazardous decomposition products should not be

produced.

Hazardous polymerization: Under normal conditions hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicity Studies: Bisphenol A-(epichlorhydrin), Bisphenol A epoxy resin

Acute Oral Toxicity – Low toxicity, LD50 >2000 mg/kg.

Acute Dermal Toxicity – Low toxicity, LD50 > 2000 mg/kg.

Medical Conditions Aggravated By Overexposure: Pre-existing skin disorders may be aggravated by over-

exposure to this product.

Potential chronic health effects:

Chromic Effects - Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Target Organs - No known significant effects or critical hazards.

Carcinogenicity - No known significant effects or critical hazards.

Mutagenicity - No known significant effects or critical hazards.

Teratogenicity - No known significant effects or critical hazards.

Developmental Effects - No known significant effects or critical hazards.

Fertility Effects - No known significant effects or critical hazards.

● Pro**REZ**

12. ECOLOGICAL INFORMATION

Environmental Effects: Toxic to aquatic organisms, and may cause long-term adverse effects in the aquatic environment. This product shows a high bioaccumulation potential. Water polluting material. May be harmful to the environment if released in large quantities.

Test	Result	Dose	Inoculum
OECD Derived	5%-Not Readily	20 mg/L Oxygen	No Data
from OECD 301F	28 days	consumption	
(Biodegradation			
Test)			

13. DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose in accordance with federal, state and local regulations.

The generation of waste should be avoided or minimized wherever possible. Empty containers should be taken to an approved waste-handling site for recycling or disposal. Incineration or landfill should only be considered when recycling is not feasible. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Refer to 40 CFR § 261.7 (residues of hazardous waste in empty containers).

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. TRANSPORT INFORMATION

Regulatory Information	UN number	Classes	Packing Group	Proper Shipping Name
DOT	NA	NA	NA	Not Regulated
TDG	NA	NA	NA	Not Regulated
IMDG	UN3082	9	III	Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A EPOXY RESIN) Marine pollutant.
IATA	UN3082	9	III	Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A EPOXY RESIN)

NA = Not Applicable



15. REGULATORY INFORMATION

Country	Regulatory List	Notification
USA	TSCA	Included on Inventory
EU	EINECS	Included on Inventory
Canada	DSL	Included on Inventory
China	SEPA	Included on Inventory
Japan	ENCS	Included on Inventory

OSHA: This product is considered to be a hazardous chemical under 29 CFR 1910.1200s.

OSHA/HCS Classification – Irritating material, Sensitizing material.

SARA 302/304/311/312 extremely hazardous substances – No ingredients listed.

SARA 311/312 Hazard Identification - No ingredients listed.

SARA 313 - No ingredients listed.

California Safe Drinking Water & Toxic Enforcement Act (Proposition 65) – WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer. This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient Name	Cancer	Reproductive	No Significant Risk Level	Maximum Acceptable Dosage Level
1-chloro-2,3-epoxypropane CAS: 106-89-8	Yes	Yes	Yes	No

Canadian WHMIS: Class D2B: Material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

16. OTHER INFORMATION

Full text of R phrases referred to under Sections 2 and 3

36/38 Irritating to eyes and skin.

43 May cause sensitization by skin contact.

Toxic to aquatic organisms, and may cause long-term adverse effects in the aquatic environment.

Full text of H statements referred to under Sections 2 and 3

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

● ProREZ

Hazardous Material Information System (HMIS):

Scale 0-4		NFPA	HMIS
4=Severe Hazard	Health	2	2
3=Serious Hazard	Flammability	1	1
2=Moderate Hazard	Reactivity	0	0
1=Slight Hazard			
0=Minimal Hazard			

THE INFORMATION AND RECOMMENDATIONS PRESENTED HEREIN ARE ACCURATE TO THE BEST OF OUR KNOWLEDGE. USER MUST CONDUCT THEIR OWN TESTS TO DETERMINE THE SUITABILITY OF THESE PRODUCTS FOR THEIR PARTICULAR PURPOSES AND USAGE. BECAUSE OF NUMEROUS FACTORS AFFECTING RESULTS, PROREZ COATINGS, LLC AND ITS AFFILIATION MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR PURPOSE, OTHER THAN MATERIAL CONFORMS TO OUR APPLICABLE CURRENT SPECIFICATIONS. PROREZ COATINGS, LLC ASSUMES NO LEGAL RESPONSIBILITY FOR USE OR RELIANCE ON THE INFORMATION CONTAINED IN THIS SAFETY DATA SHEET.

END OF DATA SHEET





ProREZ Coatings, LLC

P.O. Box 153, Cromwell, CT 06416-0153

877.511.3456 • www.prorezcoatings.com

Date Issued: 11/24/25 Version: 1.5

1. CHEMICAL PRODUCTS AND COMPANY IDENTIFICATION

Product Names/Trade Names: ProPoxy S-Hardener, ProPoxy CR S-Hardener, LWT-Hardener, EcoPoxy Hardener

Chemical Family: Modified Cycloaliphatic Amines Manufacturer's Name: ProREZ Coatings, LLC

PO BOX 153

Cromwell, CT 06416-0153 USA

General No.: (877) 511-3456 (8:00am to 5:00pm Eastern Time)

Company 24 Hour Emergency Response Information: CHEMTEL: 1-800-255-3924

Emergency telephone numbers are to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals. All non-emergency questions should be directed to customer service.

2. HAZARDS IDENTIFICATION

Emergency Overview: Danger. Causes severe skin burns and eye damage. Harmful if swallowed. May cause skin sensitization. Causes damage to organs. Toxic to aquatic life with long-lasting effects.

Component Information/Information on Non-Hazardous Components: No data available.

Classification of the substance

Hazard categories:

Skin corrosion: Category 1C Serious eye damage: Category 1 Skin sensitization: Category 1

Germ cell mutagenicity: Category 2 Reproductive toxicity: Category 1B

Specific target organ toxicity (single exposure): Category 1

Acute aquatic toxicity:

Chronic aquatic toxicity: Category 1

Label Elements

Hazardous components that must be listed on the label:

Amines, liquid, corrosive, n.o.s. (Contains 4,4-Diaminodicyclohexylmethane)

Signal word: Danger

Pictograms: GHS05 - GHS07 - GHS08











Hazard Statements:

- H302 + H332 Harmful if swallowed or if inhaled.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H360 May damage fertility or the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long-lasting effects.

Precautionary Statements

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood
- P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
- P264 Wash skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
- P281 Use personal protective equipment as required.
- P280 Wear protective gloves and eye protection.
- P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
- P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304 + P340 + P310 IF INHALED: Remove victim to fresh and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.
- P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
- P307 + P311 If exposed: Call a POISON CENTER or doctor/physician.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
- P391 Collect spillage.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an approved waste disposal plant in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None known.

Other Information: None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	% By Weight	CAS Number
PACM	30 - 45%	1761-71-3
Aliphatic Amine	10 - 30%	na
Amine-Epoxy Adduct	10 - 20%	na
Benzyl alcohol	10 - 20%	100-51-6

4. FIRST-AID MEASURES

General advice: Seek medical advice or medical attention if condition persists.

Eye contact: Rinse immediately with plenty of water for 15 minutes and seek advice of an eye specialist/physician. Continue rinsing eyes during transport to hospital. Do not remove contact lens if worn.

Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Take victim immediately to hospital to obtain medical attention. Wash clothing before reuse. Destroy or thoroughly clean contaminated shoes before reuse.

Ingestion: Rinse out mouth, spit out liquid. Do not induce vomiting and seek medical advice immediately. Never give anything by mouth to an unconscious person.

Inhalation: Move victims into fresh air. If breathing is labored, administer oxygen. If not breathing, give artificial respiration. Consult a doctor immediately.

5. FIRE-FIGHTING MEASURES

Suitable Fire Extinguishing Media: Water spray, alcohol-resistant foam, CO,, dry powder.

Unsuitable Extinguishing Media: High volume water jet.

Unusual Fire and Explosion Hazards: Firefighters should wear NFPA approved self-contained breathing apparatus and full protective clothing. Avoid contact with product. Decontaminate equipment and protective clothing prior to re-use. Toxic and irritating gases/fumes may be given off during burning or thermal decomposition.

Hazardous Decomposition Products: On combustion, toxic gases, including nitrogen oxides, carbon monoxide, carbon dioxide, tin/tin oxides.

Advice to Fire Fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire, including self-contained breathing apparatus and NFPA compliant helmet, hood, boots and gloves. Use cold water spray to cool fire-exposed containers to minimize the risk of rupture. Toxic gases/fumes may be given off during burning or thermal decomposition.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Wear appropriate personal protective equipment. Evacuate surrounding areas and isolate the area. Keep unnecessary and unprotected personnel from entering. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Implement site emergency response plan.



Environmental Precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers. Inform authorities if the product has caused environmental pollution (sewers, drains, waterways or soil).

Containment/Clean-up Measures: Cleanup personnel must use appropriate personal protective equipment. Evacuate and keep unnecessary personnel out of spill area. Remove all sources of ignition, including flames, heat, and sparks. Stop leak if without risk. Move containers from spill area. Dike or dam spilled material with non-combustible, absorbent material (e.g., sand, earth, vermiculite or diatomaceous earth) and control further spillage, where possible. Make certain the absorbent material soaks up all liquids.

7. HANDLING AND STORAGE

Handling: Do not breathe vapors or spray mist. Avoid contact with eyes or skin. Avoid contact with clothing. Use only with adequate ventilation and personal protection. Remove contaminated personal protective equipment (PPE), then wash hands and face thoroughly after handling and before eating and drinking. Keep container closed when not in use. Empty containers retain product residue and can be hazardous. Do not get in eyes, on skin or on clothing. Do not ingest. Keep away from heat, sparks, flames and other sources of ignition. Avoid release to the environment. Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination with moisture is suspected. Follow all SDS/label precautions even after container is emptied because it may retain product residues.

Storage: Keep away from food products during use and storage. Storage class (TRGS 510): non-combustible, acute toxic Category 3/toxic hazardous materials or hazardous materials causing chronic effects. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled, unapproved or reactive containers. Use appropriate containment to avoid environmental contamination. Personnel education and training in the safe use and handling of this product are required under OSHA Hazard Communication Standard 29 CFR 1910.1200.

Incompatible Materials or Ignition Sources: Stable under recommended storage conditions. Do not store together with oxidizing and acidic materials. Do not store together with caustic solutions and alkalis. Store away from food stuffs. Avoid water, air humidity, oxidizing agents, cotton waste or other combustible materials. Keep away from sources of ignition - No smoking. Additional guidance on fire and explosion protection may be found in various consensus standards, including NFPA 30, 69 and 77 and API 2003 as well as OSHA regulation 29CFR1910.106.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Special Note for Exposure Control: Consult local authorities for acceptable exposure limits.

Exposure Limits/Guidelines				
Chemical Name Result ACGIH/OSHA				
Aliphatic Amine	STELs	No data available.		
	TWAs	0.100000 mg/m³ (OSHA, ACGIH, NIOSH).		
	PEL	No data available.		
Benzyl Alcohol	STELs			
	TWAs	10 ppm		
	PEL			

Engineering measures: General dilution and local exhaust as necessary to control airborne vapors, mists, dusts, and thermal decomposition products below appropriate airborne concentration standards and guidelines. A safety shower and eye wash fountain should be readily available. To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination. Curing ovens must be ventilated to prevent the build-up of explosive atmospheres and to prevent off-gases from entering the work place.

Environmental exposure controls: Avoid release to the environment. Construct a dike to prevent spreading of spills. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Hygiene Measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating and drinking, smoking or using the lavatory and at the end of the working period. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Keep away from foodstuffs, beverages and feed.

Personal Protection:

Respiratory – In case of inadequate ventilation, wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use positive pressure supplied air respirator when airborne concentrations are not known, when airborne levels are 10 times the appropriate TLV, and when spraying is performed or product is applied by aerosol in a confined space or area with limited ventilation. If respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Contact health and safety professional or manufacturer for specific information.

Eyes/Face – Use chemical resistant goggles. Chemical safety goggles in combination with a full face shield (8-inch minimum) must be used if a splash hazard exists. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU). Contact lenses should not be worn.

Hands – Use permeation resistant gloves such as neoprene or nitrile. The glove must be impermeable and resistant to the product/the substance/the preparation. Selection of the glove material does not only depend on the material, but also on its quality and varies from manufacturer to manufacturer. The resistance of the glove material and manufacture must be determined in advance of the application/use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Skin/Body – Wear rubber or plastic apron and permeation resistant clothing, chemical-resistant gloves, and long-sleeved shirts, and pants. Gloves must be inspected prior to use. Remove and wash contaminated clothing before re-use.

General Industrial Hygiene Considerations – Keep away from food and drink. Wash hands and face after use. Educate and train workers in the safe use and handling of this product. Emergency showers and eye wash stations should be available. Follow all label instructions.



9. PHYSICAL AND CHEMICAL PROPERTIES

Form	Viscous Liquid
Color	Colorless
Boiling Point	Not available
Specific Gravity	1.02 ± 0.1
Water Solubility	Soluble
Flash Point	>93°C (>199°F) TCC

10. STABILITY AND REACTIVITY

Reactivity: No data available.

Chemical stability: Stable under normal conditions.

Possibility of Hazardous Reactions: May react with catalysts, oxidizing agents, peroxides, strong alkali and other

radical forming substances.

Conditions to avoid: Avoid oxidizing agents.

Incompatible Materials: Strong bases, strong oxidizing agents.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, and nitrogen oxides.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity:

For Aliphatic Amine:

LD50 Oral Rat 1040 mg/kg (OCED Test Guideline 401)

LC50 Inhalation Rat 2.4 mg/l (4h)

For Benzyl Alcohol:

LD50 Oral Rat 1,230 mg/kg

LD50 Rat Inhalation >4.178 mg/l 4 h

LD50 Dermal Rabbit 2,000 mg/kg

For Isophorone Diamine:

LD50 Oral Rat 1,030 mg/kg

Other Information:

On the skin: Caustic effect on skin and mucous membranes.

On the eye: Strong caustic effect.



Sensitization:

Sensitization possible through skin contact.

Sensitizing effect through inhalation is possible by prolonged and repeated exposure.

CARCINOGENICITY

This product does not contains a component that is classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification:

IARC, NTP, and OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen.

REPRODUCTIVE TOXICITY: Presumed human reproductive toxicant.

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE: No data available.

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE: No data available.

ASPIRATION HAZARD: No data available.

ADDITIONAL INFORMATION: RTECS: WH7000000.

To the best of our knowledge the chemical, physical, and toxicological properties of this product have not been thoroughly investigated.

12. ECOLOGICAL INFORMATION

Toxicity:

This product is harmful to the environment. Very toxic to fish and other aquatic life with long-lasting effects.

Persistence and degradability: According to the results of tests of biodegradability, this product is

partly biodegradable.

Bioaccumulative potential: Although the product is partly biodegradable, significant residuals remain

Other adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose in accordance with Federal, State, and Local laws and regulations. The generation of waste should be avoided or minimized wherever possible. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Empty containers should be taken to an approved waste handling site for recycling or disposal. Incineration or landfill should only be considered when recycling is not feasible. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty Container Precautions: Dispose of as unused product. Do not heat or cut container with electric or gas torch. Recondition or dispose of empty container in accordance with governmental laws and regulations. Do not reuse empty container without proper cleaning. Label precautions also apply to this container when empty.



14. TRANSPORT INFORMATION

Regulatory	UN	Classes	Packing	Proper Shipping Name
Information	number		Group	
DOT	UN2735	8	III	Polyamines, Liquid, Corrosive, N.O.S., Marine Pollutant
IMO/IMDG	UN2735	8	III	Polyamines, Liquid, Corrosive, N.O.S., Marine Pollutant
IATA/ICAO	UN2735	8	III	Polyamines, Liquid, Corrosive, N.O.S., Marine Pollutant

Special Precautions for User:

None known.

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code.

15. REGULATORY INFORMATION

State Right to Know							
Component CAS MA NJ PA							
None known	-	-	-	-			
Inventory							
Component	CAS	Canada DSL	Canada NDSL	TSCA			
Polyamine Epoxy Hardener	-	Listed	-	Listed			

HMIS Rating: 3 1 0 G NFPA Rating: 3 1 0 G

This product is in compliance with the inventory listing of the following countries:

Australia (AICS): listed/registered Japan (MITI): listed/registered Korea (KECI): listed/registered Philippines (PICCS): listed/registered

China: listed/registered

New Zealand: listed/registered

US Federal Regulations:

U.S. – CERCLA/SARA – Hazardous Substances and their Reportable Quantities: None

U.S. – SARA – Section 311/312 Hazard Categories: None

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs: None

U.S. – CERCLA/SARA – Section 313 – Emissions Reporting: None

U.S. – CERCLA/SARA – Section 313 – PBT Chemical Listing: None

U.S. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A) Components: None

U.S. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 372.65) Supplier Notification Required Components: None

U.S. Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes and Appendix VIII Hazardous Constituents (40 CFR 261): Under RCRA it is the responsibility of the person who generates a solid waste, as defined in 40 CFR 261.2, to determine if that waste is a hazardous waste.

State Regulations:

United States - California

U.S. – **California** – **Proposition 65** – **Carcinogens List:** This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

U.S. - California - Proposition 65 - Developmental Toxicity: None

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL): None

U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL): None

U.S. - California - Proposition 65 - Reproductive Toxicity - Female: None

U.S. - California - Proposition 65 - Reproductive Toxicity - Male: None

Based on information provided by ProREZ suppliers, this product is considered "DRC Conflict Free" as defined by the SEC Conflict Minerals Final Rule (Release No. 34-67716, File No. S7-40-10, Date 08-22-212).

16. OTHER INFORMATION

Hazardous Material Information System (HMIS):

Scale 0-4		NFPA	HMIS
4=Severe Hazard	Health	3	3
3=Serious Hazard	Flammability	1	1
2=Moderate Hazard	Reactivity	0	0
1=Slight Hazard			
0=Minimal Hazard			

THE INFORMATION AND RECOMMENDATIONS PRESENTED HEREIN ARE ACCURATE TO THE BEST OF OUR KNOWLEDGE. USER MUST CONDUCT THEIR OWN TESTS TO DETERMINE THE SUITABILITY OF THESE PRODUCTS FOR THEIR PARTICULAR PURPOSES AND USAGE. BECAUSE OF NUMEROUS FACTORS AFFECTING RESULTS, PROREZ COATINGS, LLC AND ITS AFFILIATION MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR PURPOSE, OTHER THAN MATERIAL CONFORMS TO OUR APPLICABLE CURRENT SPECIFICATIONS. PROREZ COATINGS, LLC ASSUMES NO LEGAL RESPONSIBILITY FOR USE OR RELIANCE ON THE INFORMATION CONTAINED IN THIS SAFETY DATA SHEET.

END OF DATA SHEET