

ProCryl CF Systems

Decorative Colored Flake MMA Broadcast Resurfacing Systems

ProCryl CF are decorative, seamless flooring systems consisting of 100% solids, fast curing, reactive, methyl methacrylate (MMA) and specially blended colored flakes (macro - 1/4" or micro - 1/16") to yield a nominal 1/16" thickness overlay. **ProCryl CF-SL** is a fast curing, high build, self-leveling, MMA slurry matrix formula broadcasted with specially blended colored flakes to yield a nominal 3/16" thickness overlay. The **ProCryl CF systems** are stylish and hard-wearing for a wide range of commercial and institutional settings.

Commercial and Institutional Flooring Use - Hard-Wearing, Durable and Stylish



BENEFITS

- ◆ Fast Cure (1 hr. return to service following finish coat)
- ◆ Applied Down to 0°F
- ◆ Indoor & Outdoor Applications
- ◆ UV Resistant
- ◆ Chemical & Stain Resistant
- ◆ Excellent Durability & Hard-Wearing
- ◆ Seamless - Easy to Clean & Maintain
- ◆ Integral Cove Base
- ◆ Colorfast Polymer Flakes
- ◆ Low Glare, Satin Finish
- ◆ Available with **Microbe•BLOK**
- ◆ Meets ADA, USDA, FDA, and OSHA Requirements

TYPICAL USES

- ◆ Laboratories
- ◆ Rest Rooms
- ◆ Lobbies
- ◆ Corridors
- ◆ Concourses
- ◆ Hospitals
- ◆ Pharmaceutical
- ◆ Locker Rooms
- ◆ Retail & Grocery Stores
- ◆ Restaurants
- ◆ Clean Rooms
- ◆ Classrooms & Cafeterias



SYSTEM DESIGN

Systems range from approximately 1/16" - 1/4" in total thickness.

- 1. ProCryl Primer** is a 100% solids, fast curing, low viscosity, reactive methyl methacrylate applied as a clear or pigmented sealer direct to concrete. The **ProCryl Primer** is installed at no less than 100 s.f./gallon. Porous concrete substrates may require two coats of primer.
- 2. ProCryl LV Binder** is a 100% solids, fast curing, low viscosity, reactive methyl methacrylate broadcasted with specially blended decorative colored flakes (macro - 1/4" or micro - 1/16") using either a single or double broadcast method to yield a 1/16" seamless resurfacing system. **ProCryl HB Binder for ProCryl CF-SL** is a fast curing, high-build, pigmented, 100% reactive methyl methacrylate slurry formulation combined with 20 lbs. of **ProFill SL** filler & aggregate. This pigmented self-leveling matrix is broadcasted with specially blended decorative colored flakes (macro - 1/4" or micro - 1/16") to yield a 3/16" seamless resurfacing system.
- 3. ProCryl KT Topcoat** is a hardwearing, clear, fast curing, methyl methacrylate grout/seal coat providing good point impact and resistance to high temperatures (up to 180°F). **ProCryl HT Topcoat** is extremely abrasion resistant and hardwearing, with good chemical, stain, and marking resistance. **ProCryl UVR Topcoat** can be used in outdoor applications for added light stability. Depending upon the required surface texture, a single or second topcoat can be applied.

