



ProREZ Coatings, LLC

P.O. Box 153, Cromwell, CT 06416-0153 877.511.3456 • www.prorezcoatings.com

TECHNICAL DATA SHEET

DESCRIPTION

ProBond Agent is a liquid additive to be used in the field for promoting better adhesion of the epoxy (ProPoxy) polymer resin to various surfaces like hard-troweled concrete, existing polymer floor coatings, ceramic or quarry tiles, or glazed blocks.

PACKAGING

Available in 1 quart and 1 gallon containers.

DOSAGE

For best results, add 1-2oz. by volume per gallon of mixed product.

PRECAUTIONS

Since surfaces and coating formulations vary considerably, each application should be verified through testing before applying a subsequent polymer coating material.

Mechanical substrate preparation followed by cleaning and solvent-wiping may still be required to ensure strong adhesion to the surface.

Gloss surfaces must be dulled prior to a coating application with the adhesion promoter.

Surfaces must be clean and completely dry prior to the application of polymer materials containing the adhesion promoter.

PHYSICAL PROPERTIES	
VOC	<250 g/L
Active Ingredients	>99%
Color	Clear, slightly yellow tint
Flashpoint	Measured at ~245°F (Closed Cup)
Odor	Ester-like

ADVANTAGES

- ◆ High bond strength hard-to-coat surfaces
- Universal to epoxy, urethane, acrylic, and waterborne dispersions
- ♦ Non-offensive odor

MIXING INSTRUCTIONS

Add 1-2 ounces of the **ProBond** adhesion promoter directly to 1 gallon of mixed resin & hardener, and blend thoroughly.

DISPOSAL

Dispose in accordance with federal, state and local regulations.

TECHNICAL SUPPORT

For any application questions, please call **ProREZ** technical support at **877.511.3456**.

SDS

PLEASE SEE SAFETY DATA SHEET (SDS) FOR SAFETY AND PRECAUTIONS. USE PRODUCT AS DIRECTED. **KEEP OUT OF THE REACH OF CHILDREN.**

Warranties: Seller warrants that its goods, as described on the face hereof, are free from any defects in material or workmanship. Seller makes no other warranty, express or implied, and all implied warranties of merchantability and fitness for a particular purpose are hereby disclaimed. Seller shall not be liable for prospective profits or special indirect or consequential damages. Seller's sole liability and buyer's exclusive remedy for breach of any warranty as expressly limited, at seller's option, to replacement at the original F.O.B. point or refund of purchase price. Seller shall not be responsible for any claim resulting from failure to utilize product in the manner in which it was intended and in accordance with instruction provided for use of product. Any claim for breach of warranty shall be deemed waived unless buyer shall give seller written notice of such claim within sixty (60) days after delivery and shall allow seller reasonable opportunity to investigate claim and inspect product.